

DB-3005D/DB-3005A VARIABLE TRIPLE OUTPUT DC POWER SUPPLY



FEATURES

- ▶ Light and Compact Design
- ▶ Overload and Reverse Polarity Protection
- ▶ Constant Voltage and Constant Current Operation
- ▶ Internal Select for Continuous or Dynamic Load
- ▶ 0.01% High Regulation
- ▶ Low Ripple and Noise
- ▶ Low Cost, High Value 0~30V, 0~10A & 0~60V, 0~5A Output.

Specification

Adjustable Triple Output Voltage (CV)	2 × 0-30V 1 × 5V Fixed
Adjustable Triple Output Current (CC)	2 × 0-5A 1 × 3A Fixed
Voltage Line Regulation ±10%	≤0.01%+3mV
Voltage Load Regulation (no load to full load)	≤0.01%+3mV
Ripple & Noise	≤1mVrms
Adjustable Current Range	5% to 100%
Current Line Regulation ±10%	≤0.2%+3mV
Current Load Regulation	≤0.2%+3mV
Display	2 × 3 Digit Volt Meter 2 × 3 Digit Ampere Meter
Available Output	Series & Parallel
ACCESSORIES	AC 120V±10%, 50/60Hz, 220V
ACCESSORIES	Instruction manual × 1. Power Supply Probe × 2 set. Power cord × 1.
POWER SOURCE	AC 220V±10%, 50/60Hz
Gross Wait	14.5Kg